


Master-PUR STEP MHR

PU Film Hose, crush-resistant, microbe & hydrolysis-resistant



Technical Drawing



Connections



Construction



Material

- spiral: plastic-profile helix
- wall: pure polyether polyurethane, microbe resistant
- Wall thickness between spirals c. 0.6 mm

Applications

- Suction & transport hose for abrasive solids, for which microbe and hydrolysis resistance is required
- Light suction hose for municipal vehicles
- Lawnmowers
- Leaf vacuums/blowers

Properties

- high tension/tear-proof
- vibration-proof
- flexible at cold temperatures
- extremely flexible
-

- crush-resistant
- mostly smooth inner lining
- free of halogens and heavy metals
- microbe and hydrolysis-resistant
- light
- smallest bending radii
- highly abrasion-resistant
- good resistance to chemicals, oil and fuel
- generally good UV and ozone resistance

Temperature Range

- -40°C to +90°C
- peaks to +125°C

Product Variations

DN	op. pressure	vacuum	bend radius	outer Ø	weight/m	article no.	stock length	max. production length
	bar	bar	mm	mm	kg		m	m
80	0,8	0,31	80	100	0,72	000400:80:x	/	25
100	0,7	0,28	98	118	0,87	000400:100:x	/	25
102	0,7	0,28	100	120	0,88	000400:102:x	/	25
120	0,63	0,23	120	140	1,05	000400:120:x	/	25
127	0,54	0,18	127	143,4	1,23	000400:127:x	/	25
150	0,51	0,17	148	168	1,28	000400:150:x	/	25
152	0,5	0,17	150	170	1,3	000400:152:x	/	25
160	0,45	0,15	160	180	1,39	000400:160:x	/	25
180	0,4	0,11	180	200	1,56	000400:180:x	/	25
200	0,31	0,08	197	217	1,7	000400:200:x	/	25
203	0,3	0,07	200	220	1,72	000400:203:x	/	25

All data refers to a medium and ambient temperature of +20 °C.

* Refers to the inner hose lining

Subject to technical changes and colour deviations.

Available on request

- Available on request in other lengths, sizes and colours, with print.