

Master-PROTECT Pipe-Bend

PU-lined pipe-bend



Material

- lining: polyurethane
- bend: DIN 2448 St 37, primed
- flange: R St 37, primed

Applications

- Pneumatic conveying plants
- Granule silos

Properties

- extremely abrasion resistant
- reduced operating costs via longer maintenance intervals
- lower risk of blockages via uniform concentration distribution and a more constant speed of transported goods
- much greater wear resistance than steel pipe bends
- pressure level PN 6 and PN 10/16
- no displacement of transport media
- significantly lower pressure loss as in deflection / impact absorbers

Temperature Range

-

- -40°C to +80°C
- peaks to +110°C

Product Variations

DN	d	PN	A	adapter outer Ø	hole circle	no. holes	old article no.	new article no.
	mm		mm	mm				
40	43	10/16	99	150	110	4	B01-040-010	004107
50	54	10/16	121	165	125	4	B01-050-010	004108
65	70	10/16	140	185	145	4	B01-065-010	004111
80	82	6	157	190	150	4	B01-080-006	004112
80	82	10/16	165	200	160	8	B01-080-010	004113
100	107	10/16	205	220	180	8	B01-100-010	004119
125	131	10/16	246	250	210	8	B01-125-010	004123
150	159	10/16	284	285	240	8	B01-150-010	004124
200	207	6	360	320	280	8	B01-200-006	004126

All data refers to a medium and ambient temperature of +20 °C.

* Refers to the inner hose lining

Subject to technical changes and colour deviations.

Available on request

- Available on request in other DN sizes and in stainless steel