



Car-Grip Quick-Fix Clamp

Special clamp for attaching Carflex Super and Master-PUR STEP hoses to mobile and stationary installations

Product Details

Construction / Material

- Specification of the connection solution: largely tension-resistant and largely leak-proof connection due to bridge profiles, individual adjustment of the clamping force possible by means of a clamping screw
- Clamp Design: clamp with turnbuckle, locking bolt detachable, clamp band with single or multiple bridges, spot welded bridge
- Material of the clamp: stainless steel 1.4301, material grade W4

Properties

- Chemical Properties: stainless
- Other: easy to assemble, can also be retrofitted to hoses that have already been installed

Operating Temperature

Delivery Information

Application Areas

Customizing Options

Article Variants

Article number	DN of the hose mm	Type	Clamping range mm
001724	75	for Carflex Super and Master-PUR Step in DN 75	75 - 82

Article number	DN of the hose mm	Type	Clamping range mm
001725	80	for Carflex Super and Master-PUR Step in DN 80	80 - 87
001726	90	for Carflex Super and Master-PUR Step in DN 90	90 - 97
001727	100	for Carflex Super and Master-PUR Step in DN 100	100 - 107
001728	110	for Carflex Super and Master-PUR Step in DN 110	110 - 117
001729	120	for Carflex Super and Master-PUR Step in DN 120	120 - 127
001730	125	for Carflex Super and Master-PUR Step in DN 125	125 - 132
001731	130	for Carflex Super and Master-PUR Step in DN 130	130 - 137
001732	140	for Carflex Super and Master-PUR Step in DN 140	140 - 147
001733	150	for Carflex Super and Master-PUR Step in DN 150	150 - 157
001734	160	for Carflex Super and Master-PUR Step in DN 160	160 - 167
001735	170	for Carflex Super and Master-PUR Step in DN 170	170 - 177
001736	175	for Carflex Super and Master-PUR Step in DN 175	175 - 182
001737	180	for Carflex Super and Master-PUR Step in DN 180	180 - 187
001738	200	for Carflex Super and Master-PUR Step in DN 200	200 - 207
001739	250	for Carflex Super and Master-PUR Step in DN 250	250 - 257

Subject to technical changes and colour deviations

Delivery Variants

Available in other lengths, other nominal diameters, with customer-specific customer-specific imprint.

Disposal instructions

After use, the product must be disposed of in accordance with the legal regulations applicable in the user's region (in Germany in accordance with the applicable Waste Catalogue Ordinance (AVV)).

Individual consultation

We offer consultation by
phone:
+49 209 97077-112

Product requests via
masterflex.de/en

Address Headquarters

Masterflex SE
Willy-Brandt-Allee 300
45981 Gelsenkirchen

